



FAT FLOOR

THE SOLUTION FOR OUTDOOR COMMUNICATION

FatFloor is designed for medium to long-term applications depending on where the product is applied. This product is available without adhesive (FatFloor) or with adhesive (FatFloor Glue) combined with AsphaltWalk smooth.

FatFloor can be used for almost all surfaces as it will be delivered without self-adhesive rear and therefore easily applied on the floor. FatFloor Glue combined with AsphaltWalk smooth are the perfect product for outside application, e.g. at (E-) petrol stations and shops where the material is under high impact. For long-term application an edge sealing is recommended. FatFloor is very resistant against wear and other influences that result from common use of the product.

Uses

- shop entrances
- car showrooms, showrooms
- museums, meeting points and other events
- petrol stations (FatFloor Glue combined with AsphaltWalk smooth)
- indoor and outdoor parkings as well as driveways (FatFloor Glue with AsphaltWalk smooth)

Features & Benefits

- simple application and removal
- very robust
- extremely slip-resistant



FAT FLOOR

THE SOLUTION FOR OUTDOOR COMMUNICATION

Durability

The durability of FatFloor is depending on the application, especially on the surface where it has been applied as well as the mechanical strain. Based on our experience we recommend a maximum use of 3 years.

Storage

Shelf life is 12 months from delivery.

Storage conditions from +15°C to +24°C and humidity between 40% and 65%.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Printing method

UV curable inks, solvent, eco-solvent and latex

Waste handling

It is recommended to handle the used material and production waste as industrial waste.

- Also available as FatFloor Glue in combination with AsphaltWalk smooth

Technical Information

Size	Width: 1.37 m	Length: 15 m	
Material	clear, slip-resistant textured vinyl available without and with adhesive (FatFloorGlue)		1300μ +/- 10μ
Adhesive	permanent acrylic solvent (FatFloorGlue)		50μ +/- 5μ
Certificate	slip resistance surface (SRT) (FatFloorGlue)		R10
Application	minimum application temperature		+10°C / +50°F

Peel Adhesion to:	Stainless Steel	Polyethylene	Powder coated surfaces *
15 minute dwell	55oz/in (66N/100 mm)	20oz/in (22N/100mm)	40oz/in (44N/100mm)
24 hours dwell	75oz/in (82N/100 mm)	25oz/in (27N/100 mm)	55oz/in (60N/100 mm)

Chemical resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	R	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion
I = recommended for intermittent exposure only
NR = not recommended